BKG® Combi-Line™

Underwater Pelletizing System

Throughput range up to 2,000 kg/hr (4,400 lb/hr)

Processes

- Masterbatch
- Compounding
- Recycling

Materials

- All materials which behave like thermo-plastic polymers (PE, PP, PS, ABS, SAN, PA, PET, PC, POM, TPE, TPU, EVA, APAO, PBT, PMMA, EPDM)

Features

- Modular design
- Completely skid-mounted
- Dual door dryer access for easy cleaning
- Optional Fines Removal Sieve (curved screen) with filtration level 150µm

Benefits

- Compact footprint
- Flexibility for material and / or color changes
- Easy and fast cleaning of the system components
- Easy operation, simple handling

Model	Pellet Dryer	Capacity
Combi-Line™ 1	TVE 1001 ED	< 1,200 kg/hr (2,600 lb/hr)
Combi-Line™ 2	TVE 2000 ED	< 2,000 kg/hr (4,400 lb/hr)

Nordson BKG GmbH
Hessenweg 3-5
48157 Münster / Germany
Phone +49.251.26501.0

USA
Phone +1.828.326.9888

China
Phone +86.21.5785.091.8

Japan
Phone +81.3.5762.2770

nordsonpolymerprocessing.com | info@nordsonpolymerprocessing.com

BKG is a trademark of Nordson Corporation, registered in the United States and other countries.

© 2021 Nordson BKG GmbH
Printed in USA
01/2021