



Compact Overhead



Italian Leader Worldwide

EUROMAC
SLITTERS REWINDERS

Euromac Costruzioni Meccaniche S.r.l. - Strada Statale 31 n.6 - 15030 Villanova Monf. - Italia
TEL. +39 0142.483195 - FAX +39 0142.483611 - www.euromacslitters.com • euromac@euromacslitters.com



TB-3p Compact Overhead

oscillating Razorblades and/or Shear-cut rotary blades

- Knifeholders on shaft or linear bearing guides
- Specific web path for Wrap-cut or Tangent-cut
- Manual or semi-automatic positioning of slitting blades.

UNWIND - Integrated Shaftless or shafted unwinder

- Dancing roller for tension control
- Pneumatic Brake or electric Motor
- Automatic webguiding system.

SLITTING - Slitting system with

WEB PATH - Compact Overhead web path

- Aluminum idler rollers
- Driven main pull roll with own pressure roller or "S" wrap.

REWIND - Duplex rewind with lay-on rolls

- Differential Friction

shafts or Air expanding shafts

- Independent lay-on rollers with pneumatic pressure control
- Tension regulation by multiple systems
- Manual core positioning or assisted by laserpointers or by automatic loader
- Roll offloading by twin bar device or motorised trolley.

AUTOMATION - PLC for all machine functions and controls

- Touch screen digital operator panel
- Modem for remote monitoring.



MAIN SPECIFICATION	Standard	Option
Maximum web widths	600 to 2.000 mm	(or Custom)
Maximum rewind diameter	600 and 800 mm	(or Custom)
Maximum unwind diameter	800 and 1.000 mm	(or Custom)
Webguide stroke	± 50 mm	(or Custom)
Core diameter	76, 152 mm	(or Custom)
Maximum working speed	350-750 m/min	(or Custom)
Web tension range	Customised	
Rewind system	Centre and Lay-on rolls	(Gap rewind)
Slitting	Oscillating razors	(Shear)
Material	Monolayers (CPP, BOPP, BOPA, BOPP, PVC, PET), Laminates, Coextrusion films, Paper, Paper/PE, Metalised films. Aluminum foil.	
Best choice for Aluminum foil, Aluminum laminates		